


MODEL AT1616L



- NOTES:
- 1) MIN ISOLATED INPUT CURRENT = 1.2MA
 - 2) MIN CURRENT TRANSFER RATIO = 20%
 - 3) MAX. POWER (2 RESISTORS) = 0.25W
 - 4) R = 6800 X 2, 18-60V, 1.2-4.5MA
 - 5) R = 5100 X 2, 13-51V, 1.2-5.0MA
 - 6) R = 4700 X 2, 12-48V, 1.2-5.1MA
 - 7) R = 3300 X 2, 9-40V, 1.2-6.1MA
 - 8) R = 2200 X 2, 7-32V, 1.2-7.3MA*(STD.)
 - 9) R = 1500 X 2, 5-27V, 1.2-9.0MA
 - 10) R = 1000 X 2, 3.8-22V, 1.2-11.0MA

This drawing is the property of R. E. SMITH and shall not be used except with the written permission of R. E. SMITH, no copies shall be made of it and all proprietary rights in the matter contained in this drawing are the property of R. E. SMITH. COPYRIGHT - R. E. SMITH, 1998		DRAWN BY RES	SUBJECT 16-IN/16-OUT PCB	
		DATE 8-9-98	FOR INPUT SECTION	
		SCALE NONE	RES R. E. SMITH 4381 TYLERSVILLE RD. HAMILTON, OHIO 45011	
SHEET 1 OF 1	AT1616LI	CHKD. BY RES	DWG. NO. AT1616LI	REV. A