
MODEL USN88RC
MAX232
J22
J18
J21
J6
J2
J1
J3
J4
J5
J7
J8
J15
J23
J24
J25
J26
J43
DSR BLU
RXD YEL
TXD GRN
GND RED
RTS BLK
CTS WHT
6 DTR
5 TXD
4 RXD
R19 2.2K
R18 2.2K
R17 2.2K
4.0MHZ
4.7K
R2
DS 1233
U2 70L05
LDIN
GRN
RED
DATA TPIC-3
DE/ TPIC-9
LDCLK TPIC-12
DIN
CLK
EECLK
* 10K PULLUP
RP1=R1-X, RP2=R2-X
R1 2.2K
75ALS180
R10 39K
R11 39K
R12 2.2K
R13 2.2K
0.1UF
C4
C5
R16 120
R8 10
IN4004
P6KE12A
P6KE6.8A
RJ-11
RJ-11
TX
RX
RED
GRN
R14 390
R15 390
R5 390
R6 390
(B3) RED
(B4) GRN
TPIC-13 CLK
(B5) LDIN
(A1) CLK
(A0) DIN
R3 10K
R4 10K
R7 390
(A2) EECLK
4021B
4021B
SEE USN88RCX SHEET
INPUT SECTION
24C02A
OPTIONAL EEPROM
* 22K PULLUP
RP3, PIN-1 = +5V
IN4004
WAGD
2.1MM PIN
LM2574
SWITCHER
330uH
1N5819
C3 .33UF
C2 220UF
C1 220UF
INSTALL REMOVE
J1 MASTER SLAVE
J2 2-WAY 1-WAY
J3 COMPUTER INDEPENDENT
USN88RC
USN88RCX
USN88RSS
U88RCWD
U88RCWD1
This drawing is the property of R. E. SMITH and shall not be used except with the written permission of R. E. SMITH, no copies shall be made of it and all proprietary rights in the matter contained in this drawing are the property of R. E. SMITH.
COPYRIGHT - R. E. SMITH 1995
DRAWN BY RES
DATE 6-7-95
SCALE NONE
CHKD. BY RES
SUBJECT 8-IN, 8-OUT, DIG.
FOR CORE PROCESSOR
RES R. E. SMITH 4761 TYLERSVILLE RD. HAMILTON, OHIO 45011
DWG NO. USN88RC
REV. B
SHEET 1 OF 1
USN88RC