



MODEL DIACR44

DUAL ISOLATION
3000VDC FOR 1 SEC.

THIS UNIT CAN BE USED AS AN RS422 TO RS422 REPEATER, AS AN RS485 TO RS485 REPEATER, OR AS AN RS485 (2-WIRE) TO RS422 (4-WIRE) CONVERTER. THE RS422 TX FUNCTION CAN BE GATED ON OR SELECTED FOR ALWAYS ON MODE OF OPERATION.

R. E. SMITH
4311 TYLERSVILLE ROAD
HAMILTON, OHIO 45011
513-874-4796

www.rs485.com

■ JUMPER INSTALLED (FACTORY SETTING)
RS485=J1B=J6A=J7A=INSTALLED=CHANNEL A
RS485=J11B=J16A=J17A=INSTALLED=CHANNEL B

This drawing is the property of R. E. SMITH and shall not be used except with the written permission of R. E. SMITH, no copies shall be made of it and all proprietary rights in the matter contained in this drawing are the property of R. E. SMITH. COPYRIGHT - R. E. SMITH, 1998-2002		DRAWN BY RES	SUBJECT DUAL-ISO REPEATER
DATE 9-14-02		FOR 3000VDC ISOLATED	
SCALE NONE		RES R. E. SMITH 4311 TYLERSVILLE RD. HAMILTON, OHIO 45011	DWG. NO. DIACR44
SHEET 1 OF 1		CHKD. BY RES	REV. C